



SUMMIT SERIES SINGLE RADIO DETAILED SPECIFICATIONS

SUMMIT OUTDOOR WIRELESS PRODUCT ENCLOSURE PHYSICAL SPECIFICATIONS

Size	12 " x 12 " x 3 " with integrated antenna
Weight	6 lbs.
Mounting	Wall and pole mount
Pole Size	.5 to 3 " outside diameter
External Connectors	RJ45 Power over Ethernet and N Type Female
AZ/EL Control	Both
Temperature	-55C † 85C
Vibration	MIL-STD-810F and IEC 60721-3-4 4M5 random
Shock Mechanical	MIL-STD-810F and IEC 60721-3-4 4M5
Humidity	100%
Water Ingress	IP67 / NEMA6 / IEC 529
Solar Radiation	ASTM G53 1000h
Ice Load	25mm radial
Salt Fog	MIL-STD-810F and IEC 68-2-11 Ka 500 hours

SUMMIT OUTDOOR WIRELESS PRODUCT INTERFACE FREQUENCY SPECIFICATIONS

FREQUENCY RANGE	2.412 TO 2.462 GHz	4.475 TO 4.725 GHz	4.920 TO 5.895 GHz
Peak Transmit Power & Transmit Power Control (TPC)	28 dBm (600mW) – Yes	24 dBm (250mW) – Yes	27 dBm (500mW) – Yes
Modulation Type with DFS Support	OFDM – No	OFDM – No	OFDM – Yes
IEEE Protocol	802.11 b/g and proprietary	802.11 a and proprietary	802.11 a and proprietary
Data Rates	6Mbps, 9Mbps, 12Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps	6Mbps, 9Mbps, 12Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps	6Mbps, 9Mbps, 12Mbps, 24Mbps, 36Mbps, 48Mbps, 54Mbps
TX Channel Width	5, 10, 20, and 40 MHz	5, 10, 20, and 40 MHz	5, 10, 20, and 40 MHz
Security	WPA, WPA2, AES-CCM & TKIP encryption, 802.1x, 64/128/152bit WEP	WPA, WPA2, AES-CCM & TKIP encryption, 802.1x, 64/128/152bit WEP	WPA, WPA2, AES-CCM & TKIP encryption, 802.1x, 64/128/152bit WEP
Receiver Sensitivity	-74 to -97 dBm	-73 to -92 dBm	-74 to -94 dBm
Outdoor Range (Antenna Dependent)	30 miles	30 miles	30 miles
FCC Part 15	Yes	Yes	Yes
CE Mark	Yes	Yes	Yes
Industry Canada RSS-210	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes
ESD/EMP Protection	Yes	Yes	Yes
MTBF Rate	160,000 hours	160,000 hours	160,000 hours

see reverse





SUMMIT SERIES SINGLE RADIO DETAILED SPECIFICATIONS

SUMMIT OUTDOOR WIRELESS PRODUCT IEEE NETWORKING STANDARDS AND DESCRIPTION

802.1d	Ethernet and bridging
802.1p	Traffic prioritization
802.1q	Virtual Local Area Networks (VLAN)
802.1s	Spanning tree protocol
802.1w	Rapid spanning tree protocol
802.3ab	Gigabit ethernet
802.3ac	Q-tag support for 802.1Q VLAN information and 802.1p traffic priority information
802.3ad	Link aggregation for parallel links (now IEEE 802.1AX)
802.3i	10 Mbps ethernet
802.3u	100 Mbps ethernet with auto-negotiation
802.3x	Full duplex and flow control
802.11e	WMM and QoS
802.11h	DFS and TPC

INCLUDED CONFIGURATION AND CONTROL SOFTWARE FEATURES

NAME	FEATURES
SpeedCONFIG®	IP discovery tool
	Local and remote configuration
	Bandwidth test tool (on board and external)
	Spectrum analysis
	Real Time Received Signal Quality Indicator (RSSI)
	Client Connection Quality (CCQ)
	Antenna alignment tool with audio
System file configuration management and scripting	
Summit View Network Monitoring System	IP discovery tool
	Network and node management with link to configuration tools
	Real Time Received Signal Quality Indicator (RSSI)
	Real time wireless interface data rate monitoring
	Wireless event reporting tool (audio and email capability)



MADE IN THE USA
SDVOSB
CAGE CODE: 09FR8
9001:2008
AS9100C
J-STD-001



©2011 Mountain Secure Systems, a Subsidiary of Phillips Service Industries

1350 Kansas Avenue,
Longmont, CO 80501 USA
888-884-9344

MountainSecureSystems.com

ISO 9001:2008 AS9100C CAGE 09FR8 SDVOSB

